9001SKR2U 30MM PUSH BUTTON HEAD EXTENDED **GUARD**





Main Range of product Harmony 9001SK Product or component Head for spring return push-button type Device short name 9001SK Operator profile Recessed, unmarked Operator additional High guard with set of 7 color caps information

Com	-		1
L.Am	വല	me	ntarv
OULL	$\mathbf{p}_{\mathbf{i}}\mathbf{c}$		ntany

Mounting diameter	1.18 in (30 mm)
Shape of signaling unit head	Round
Type of operator	Spring return
Net Weight	0.11 lb(US) (0.05 kg)

Ordering and shipping details

Category	21429 - 9001 SK,SKY	
Discount Schedule	CS1	
GTIN	00785901524380	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.11 lb(US) (0.05 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

3		
Unit Type of Package 1	PCE	
Package 1 Height	2.00 in (5.08 cm)	
Package 1 width	2.30 in (5.842 cm)	
Package 1 Length	2.90 in (7.366 cm)	

Offer Sustainability


Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	


China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
Contractual warranty		
Warranty	18 months	

Product data sheet Dimensions Drawings

9001SKR2U

Dimensions






9001SKR2U

Contact Block Mounting Position

Top and Rear views



- It is possible to mount up to 3 levels of contacts blocks (maximum of 6 contacts blocks)
- (1) (2) (3) Operator
- Locating notch
- Side 1
- (4) (5) Side 2