Product data sheet Characteristics

XS9C4A1NCG13

inductive sensor XS9 40x40x117 - PBT - Sn20 mm - 12..24VDC - terminals





Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Device application	Factor 1 (Fe/Nfe) Welding machine
Sensor name	XS9
Sensor design	Form 40 x 40 x 117
Size	117 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Plastic
Enclosure material	PBT
Type of output signal	Discrete
Wiring technique	4-wire
[Sn] nominal sensing distance	0.79 in (20 mm)
Discrete output function	1 NO + 1 NC
Output circuit type	DC
Discrete output type	NPN
Electrical connection	Screw-clamp terminals, 4 x 1.5 mm ²
[Us] rated supply voltage	1224 V DC reverse polarity protection
Switching capacity in mA	<= 200 mA overload and short-circuit protection
IP degree of protection	IP67 IEC 60529 IP65 IEC 60529 IP69K DIN 40050

Complementary

Complementary		
Detection face	5 positions turret head	
Front material	PBT	
Operating zone	0.000.63 in (016 mm)	
Differential travel	315% of Sr	
Repeat accuracy	<= 3% of Sr	
Electromagnetic compatibility	Immunity to magnetic fields 250 mT	
Cable entry number	1 tapped entry Pg 13.5 cable gland	
Status LED	Supply on 1 LED green) Output state 1 LED yellow)	
Supply voltage limits	1036 V DC	
Switching frequency	<= 250 Hz	
Maximum voltage drop	<2 V closed)	
Current consumption	030 mA no-load	
Maximum delay first up	15 ms	
Maximum delay response	2.5 ms	
Maximum delay recovery	2.5 ms	
Marking	CE	
Height	1.57 in (40 mm)	
Length	1.57 in (40 mm)	

Width	4.61 in (117 mm)
Net weight	0.54 lb(US) (0.244 kg)
Environment	
Product certifications	UL CSA CCC
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)
Vibration resistance	25 gn +/- 2 mm 1055 Hz)IEC 60068-2-6
Shock resistance	50 gn 11 msEN 60068-2-27
Ordering and shipping details	
Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	03389119086462
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	FR
Dankin a Haife	
Packing Units Unit Type of Package 1	PCE
Package 1 Height	1.97 in (5 cm)
Package 1 width	1.97 in (5 cm)
Package 1 Length	5.83 in (14.8 cm)
. donago i Estigui	0.00 III (1.1.0 oiii)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Mercury free	Yes
RoHS exemption information	∰Yes
Environmental Disclosure	Product Environmental Profile
	Product Environmental Profile
Contractual warranty	

18 months

Warranty