Product data sheet Characteristics

6275AXXSZS-AC90

Relay, Legacy, solid state, SPST NO, 75A, 24...280 VAC, 90...280 VAC Uc, SCR AC zero cross, screw terminal



Main	
Range	Legacy
Product Type	Solid state relay
Nominal Output Current	75 A AC
Network Number of Phases	1 phase
Mounting Support	Panel
Output Voltage	24280 V AC
Control Circuit Voltage	90280 V AC

Complementary

Complementary	
Input Impedance	13000 Ohm
Holding Current	40 mA
Input Current Limits	24 mA 240 V AC typical
Switch Function	SPST
Contacts Type and Composition	NO
Protection Technology	Current limiter
Tightening Torque	10 lb.in input 20 lb.in output
Connections Terminals	Input screw clamp terminal, 1 Output screw clamp terminals, 1
Screw Type	M3.5 M6
Local Signalling	Input status 1 LED green)
Switching Device	SCR output Zero voltage switching
Maximum Peak Voltage	600 V
Surge Current	1000 A 16.6 ms
Must Release Voltage	10 V
Voltage Drop	<1.6 V on-state for AC
Power Factor	With maximum load
Insulating Resistance	1 GΩ
Thermal Resistance	0.31 °C/W
Maximum I²t for fusing	4150 A².s 8.3 ms
Leakage Current	10 mA at off-state
DV/dt	500 V/µs off-state at maximum rated voltage
Response Time	10 ms turn-on) 40 ms turn-off)
Dielectric Strength	4000 V between input and ground 4000 V between output and ground 4000 V between input and output
Height	1.39 in (35.3 mm)
Width	1.85 in (47.1 mm)
Depth	2.30 in (58.4 mm)
Product Weight	3.70 oz (105 g)

Environment

Product Certifications	UL CSA CE
IP Degree of Protection	IP20
Ambient Air Temperature for Operation	-40176 °F (-4080 °C)
Ambient Air Temperature for Storage	-40257 °F (-40125 °C)

Ordering and shipping details

GTIN	03606480277382
01111	00000400211002

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
	· · ·

Connections and Wiring Diagrams

