



Main

| | |
|-------------------------------|--|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCMD |
| Design | Miniature |
| Body type | Fixed |
| Associated head | ZCE29 ZCE02 ZCE06 ZCE62 ZCE09 ZCE13 ZCE67 ZCE10 ZCE14 ZCE07 ZCE08 ZCE65 ZCEG1 ZCEF0 ZCE24 ZCE11 ZCE27 ZCE64 ZCEF2 ZCE28 ZCE66 ZCE01 ZCE63 ZCE21 ZCE106 ZCE016 ZCE026 |
| Body material | Zamak |
| Number of poles | 2 |
| Contacts type and composition | 2 NC |
| Contact operation | Snap action |

Complementary

| | |
|--|---|
| Product compatibility | XCMD |
| Electrical connection | Male connector AMP connector, 4 pins |
| Contacts insulation form | Zb |
| Contacts material | Silver plated contacts |
| Positive opening | Without |
| Minimum actuation speed | 0.01 m/min |
| [Ie] rated operational current | 1 A 24 V, DC-13 EN/IEC 60947-5-1 appendix A 3 A 24 V, AC-14 IEC 61131-2 Type 1 |
| [Ithe] conventional enclosed thermal current | 6 A |
| [Ui] rated insulation voltage | 24 V 3)UL 508 24 V 3)CSA C22.2 No 14 24 V 3)IEC 60947-5-1 |
| Maximum resistance across terminals | 0.025 Ohm IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 800 V IEC 60664 |
| Short-circuit protection | 6 A cartridge fuse gG |

| | |
|-----------------------|---|
| Electrical durability | 10000000 cycles, DC-13 24 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C |
| Maximum Width | 1.26 in (32 mm) |
| Height | 2.68 in (68 mm) |
| Depth | 0.63 in (16 mm) |
| Net Weight | 0.14 lb(US) (0.065 kg) |

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |

Ordering and shipping details

| | |
|-----------------------|----------------|
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 3.25 oz (92 g) |

Packing Units

| | |
|------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 6.69 in (17 cm) |
| Package 1 width | 27.95 in (71 cm) |
| Package 1 Length | 20.47 in (52 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |