

SUA1500X93

APC Smart-UPS 1500VA USB 120V
SHIPBOARD (Not for sale in CO, VT or WA)
(Not for sale in CO, VT or WA)



Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

General

Provided equipment	Smart UPS signalling RS-232 cable User Manual USB cable
Product web sub-family	TAA compliance
Performance multiplier	1
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Telecom Server
UPS size	WS
Value multiplier	1
Variant option	Shipboard

Physical

Cable length	6 ft (1.83 m)
Color	Black
Depth	17.28 in (43.9 cm)
Height	8.50 in (21.6 cm)
Mounting location	Front
Mounting preference	No preference
Net Weight	53.11 lb(US) (24.09 kg)
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Maximum Width	6.69 in (17 cm)

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Efficiency at full load	75...154 V adjustable 82...144 V
Number of cables	1
Nominal Input Voltage	120 V

Output

Kw Rating	980 W
Max Configurable Power (Watts)	980 W
Harmonic distortion	Less than 5%
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Topology	Line Interactive
Waveform Type	Sine wave
Nb of power socket outlets	8 NEMA 5-15R
Curve equation	Efficiency
Curve fixed loss	0.0201
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0
Curve square loss	0.0134
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the US DOE Test Procedure for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 120V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	120 V
Maximum configurable power in VA	1440 VA
Rated power in VA	1440 VA

Conformance

Product certifications	CSA TAA compliance
Standards	UL 1778

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA
Heat dissipation	135 Btu/h
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Liquid Electrolyte Value	0
Battery curve	Z
Battery Charge Power (Watts)	136 W rated
Battery power in VAH	408 VAh runtime
Battery life	3...5 year(s)
Extendable Run Time	0

Communications & Management

Free slots	0
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	320 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	00731304195061
Package weight(Lbs)	58.11 lb(US) (26.36 kg)

Packing Units

Package 1 Height	15.00 in (38.1 cm)
Package 1 width	12.99 in (33 cm)
Package 1 Length	22.99 in (58.4 cm)
Number of Units in Package 3	24

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------