ZCMC29L1

pre-cabled connection ZCMC - 2 Poles - PvR -1 m





Main

Range of product	OsiSense XC
Product or component type	Pre-cabled connection
Component name	ZCMC
Associated body	ZCMD29
Number of poles	2
Contacts type and composition	2 NC
Contact operation	Snap action

Complementary

Product compatibility	XCMD29
Electrical connection	Cable
Cable length	3.28 ft (1 m)
Wire insulation material	PvR

Ordering and shipping details

Category	22413 - LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	T
GTIN	00785901660248
Nbr. of units in pkg.	1
Package weight(Lbs)	0.06 lb(US) (0.03 kg)
Returnability	No
Country of origin	ID

Packing Units

Package 1 Height	0.200 dm	
Package 1 width	1.300 dm	
Package 1 Length	1.250 dm	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. This documentation is not integrated to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Warranty 18 months