



Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	UL Listed
Enclosure Rating	NEMA 3R galvanized steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	3
Voltage Rating	480 V AC 250 V DC
Wire Size	AWG 6...300 kcmil copper or aluminium

Complementary

Maximum Horse Power Rating	15 hp 480 V AC 50...60 Hz 3 phase NEC 430.52
Maximum Width	24 in (609.60 mm)
Height	32.5 in (825.50 mm)
Depth	10.63 in (270.00 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil



Ordering and shipping details

Category	00133 - DT SWITCH,NEMA3R
Discount Schedule	DE1
GTIN	00785901453819
Nbr. of units in pkg.	1
Package weight(Lbs)	72.9 lb(US) (33.07 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.00 in (27.94 cm)
Package 1 width	23.10 in (58.674 cm)
Package 1 Length	34.00 in (86.36 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------