



## Overview

Lead time	Usually in Stock
-----------	------------------

## Physical

Color	Black
Depth	2.72 in (6.9 cm)
Height	1.73 in (4.4 cm)
Net Weight	0.40 lb(US) (0.18 kg)
Maximum Width	0.75 in (1.9 cm)

## Output

Number of power socket outlets	1
--------------------------------	---

## Environmental

Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	23...113 °F (-5...45 °C)
Storage altitude	0...10000 ft (0.00...3048.00 m)

## Surge Protection and Filtering

Data Lines Protected (multi-line only)	1-8
NM Surge Response Time (ns)	1 ns common mode
Peak current	0.25 kA common mode 0.2 kA normal mode

## Ordering and shipping details

GTIN	00731304203384
Package weight(Lbs)	0.90 lb(US) (0.41 kg)

## Packing Units

Package 1 Height	3.90 in (9.9 cm)
Package 1 width	1.30 in (3.3 cm)
Package 1 Length	3.74 in (9.5 cm)
SCC14	30731304203385
Number of Units in Package 2	96
Package 2 Weight	13.67 lb(US) (6.20 kg)
Package 2 Height	8.125 in (206.38 mm)
Package 2 width	16.25 in (412.75 mm)
Package 2 Length	25.125 in (638.18 mm)
Number of Units in Package 3	28

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	Lifetime
----------	----------