

6340AXXMDS-DC3

Relay, Legacy, solid state, SPST NO, 40A, 3...200 VDC, 3...32 VDC U_c, MOSFET DC switching, screw terminal



Main

Range	Legacy
Product Type	Solid state relay
Nominal Output Current	40 A DC
Network Number of Phases	1 phase
Mounting Support	Panel
Output Voltage	3...200 V DC
Control Circuit Voltage	3.5...32 V DC

Complementary

Input Impedance	1 kOhm
Holding Current	20 mA
Input Current Limits	10 mA DC typical
Switch Function	SPST
Contacts Type and Composition	NO
Protection Technology	Current limiter
Tightening Torque	10 lb.in input 20 lb.in output
Connections Terminals	Input screw clamp terminal, 1 Output screw clamp terminals, 1
Screw Type	M3.5 M6
Local Signalling	Input status 1 LED green)
Switching Device	Mosfet output DC switching
Maximum Peak Voltage	200 V
Surge Current	90 A 16.6 ms
Must Release Voltage	1 V
Voltage Drop	<2.8 V on-state DC
Power Factor	With maximum load
Insulating Resistance	1 GΩ
Thermal Resistance	1.06 °C/W
Leakage Current	8 mA at off-state
Response Time	600 μs turn-on) 2.6 ms turn-off)
Dielectric Strength	2500 V between input and ground 2500 V between output and ground 2500 V between input and output
Height	1.39 in (35.3 mm)
Width	1.85 in (47.1 mm)
Depth	2.30 in (58.4 mm)
Product Weight	4.76 oz (135 g)

Environment

Product Certifications	UL CSA CE
IP Degree of Protection	IP20
Ambient Air Temperature for Operation	-40...176 °F (-40...80 °C)
Ambient Air Temperature for Storage	-40...212 °F (-40...100 °C)

Ordering and shipping details

GTIN	03606480277412
------	----------------

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Wiring Diagrams

