Product data sheet Characteristics

LA36150 3P 150A, 600V, LA FA/LA MOLDED CASE CIRCUIT BREAKER



Main	
Product or Component Type	Circuit breaker
Range	I-Line
Trip Unit Technology	Thermal-magnetic
Circuit Breaker Rating Code	A

Complementary

Rated Current	150 A	
Number of Poles	3P	
Breaking Capacity Interrupt Rating	42 KA 120 V AC 42 KA 240 V AC 30 KA 480Y/277 V AC 10 kA 125 V DC	
Rated Operational Voltage	600 V AC 250 V DC	
Mounting Mode	I-Line	
Electrical Connection	Lugs load I-Line connection line	
Wiring Configuration	3-wire	
Magnetic Hold Current	750 A	
Magnetic Tripping Current	1500 A	
Terminal Type	AL400LA	
AWG Wire Gauge	AWG 1600 kcmil aluminium/copper)1 AWG 1250 kcmil aluminium/copper)2	
Height	11 in (279.40 mm)	
Width	6 in (152.40 mm)	
Depth	5.84 in (148.34 mm)	

Environment

Ordering and shipping details

01040 - LA/LH BRKR, SW, MAG-GARD
DE2
00785901339274
1
18.08 lb(US) (8.20 kg)
Yes
MX

Offer Sustainability

Contractual warranty

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

18 months