LK4DUKR1

TeSys LK disconnect switch kit, disconnect switch, 3 P, 30 A, shaft, guide cone, red handle, NEMA 1, 3R and 12



Main	
Range	TeSys
Product or component type	Disconnect Switch
Disconnector device type	Non-fusible disconnect switch
Suitability for isolation	Yes
Handle colour	Red
Handle front plate colour	Yellow

Complementary

3P
AC
50/60 Hz
30 A600 V AC UL 30 A600 V AC CSA 32 A400 V AC AC-22A IEC 32 A400 V AC AC-23A IEC 32 A690 V AC AC-22A IEC 32 A690 V AC AC-23A IEC
600 V AC 50/60 Hz
15 KW 400 V 18.5 KW 500 V 25 kW 690 V
10 Hp 240 V 30 A AC 20 Hp 480 V 28 A AC 25 hp 600 V 28 A AC
5.5 kA
10000 cycles
6000 cycles
Lugs-ring terminals 1 0.01 in² (4 mm²)
3.13 in (79.5 mm)

Environment

NEMA 1/12/3R
UL98 CSA C22.2 No 4 IEC 60947-3
UL CSA
4.92 in (125 mm)
2.52 in (64 mm)
_

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	l11
GTIN	00785901733478
Nbr. of units in pkg.	1
Package weight(Lbs)	2.46 lb(US) (1.12 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	3.60 in (9.144 cm)
Package 1 width	5.50 in (13.970 cm)
Package 1 Length	17.80 in (45.212 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months