


Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
LC1D09JL



Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone: +1 8773425173
Email: CCC@us.schneider-electric.com

| Technical Information: | |
|------------------------|--|
| Rating: | 600V / 9A |
| UL File/CCN: | E164862 / NLDX |
| CSA File: | LR43364 3211 04 |
| Meets Standards: | IEC 60647-4 |
| Weight: | 0.71 lb (0.32 kg) |
| Termination Method: | Screw Clamp |
| Wire Size: | Power: #10 - #18 AWG Control: #10 - #18 AWG |
| Terminal torque: | Power: 15 lb-in (1.7 Nm) Control: 15 lb-in (1.7 Nm) |
| Mounting Hwd.: | 35mm DIN Rail, #8 screw |

Specification:

| | |
|----------------|---|
| Description | TeSys D IEC Contactor - 9A - Vdc Coil |
| Type | TeSys D IEC Contactor - 9A - 12Vdc Coil |
| Voltages Code: | JL at 12VDC |

Coil Consumption: Inrush 2.4 W
Sealed 2.4 W

| Single Phase | | Three Phase | | | |
|--------------|------|-------------|------|------|--------|
| 115V | 230V | 200V | 230V | 460V | 575V |
| 0.5 HP | 1 HP | 2 HP | 2 HP | 5 HP | 7.5 HP |