

TERMINAL LUG DATA ±			
AMPERES	MAX WIRE	MIN WIRE	TYPE
30	# 2 AWG	# 14 AWG	CU
60	# 2 AWG	# 14 AWG	CU


APPLETON RECEPTACLE

DUAL DIMENSIONS: INCHES
MILLIMETERS

NOTES:
FINISH:
SWITCH – GRAY BAKED ENAMEL ELECTRODEPOSITED OVER CLEANED PHOSPHATIZED STEEL.
RECEPTACLE – EPOXY POWDER COATING OVER COPPER-FREE CAST ALUMINUM.
UL LISTED – FILE E85159
CSA CERTIFIED
SUITABLE FOR USE AS SERVICE EQUIPMENT.
SHORT CIRCUIT RATING:
10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES.
200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R OR J FUSES
WHEN USED IN AN OUTDOOR APPLICATION REMOVE DRAIN IN BOTTOM ENDWALL..
WHEN MOUNTING THESE SWITCHES, ALLOW 4.00/[102] MIN CLEARANCE BETWEEN ENCLOSURES FOR
OPENING OF SIDE HINGED DOOR.
■ FOR SINGLE PHASE HP RATINGS USE 2 OUTER SWITCHING POLES.
◆ USE 2 OUTER SWITCHING POLES.
± LUG SUITABLE FOR 60°C OR 75°C COPPER CONDUCTORS.

CATALOG NUMBER	VOLTAGE RATING	AMPERE RATING	WIRING DIAG	HORSEPOWER RATINGS ■									
												250 VDC ◆	
				480VAC				600VAC					
				STD		MAX		STD	MAX				
				1 Ø	3 Ø	1 Ø	3 Ø	3 Ø	1 Ø	3 Ø	STD	MAX	
H361AWAVW	600VAC;250VDC	30	A	3	5	7 1/2	15	7 1/2	–	20	5	–	
H362AWAVW	600VAC;250VDC	60	A	5	15	20	30	15	–	50	10	–	
HU361AWAVW	600VAC;250VDC	30	B	–	–	10	20	–	15	30	–	5	
HU362AWAVW	600VAC;250VDC	60	B	–	–	25	50	–	30	60	–	10	

HEAVY DUTY SAFETY SWITCHES
WITH RECEPTACLE
30–60 AMPERES
ENCLOSURE – NEMA TYPE 12 INDUSTRIAL AND
NEMA TYPE 3R RAINIGHT


by Schneider Electric

DWG# 1934V
NO.