



Note:  
- Drawings Not To Scale  
- Drawings Subject to Change Without Notice  
- Dimensions are inches next to [Millimeters]

Part No.:  
**LC1D256M7**

**Schneider Electric**  
Schneider Electric United States  
North American Division  
Boston One Campus  
800 Federal Street  
Andover, MA 01810, USA  
Phone: +1 8773425173  
Email: CCC@us.schneider-electric.com

Technical Information:	
Rating:	600V / 25A
UL File/CCN:	E164862 / NLDX
CSA File:	LR43364 3211 04
Meets Standards:	IEC 60647-4
Weight:	0.82 lb (0.37 kg)
Termination Method:	Ring Tongue
Wire Size:	Power: Lug Size 0.32 in (8mm) Control: Lug Size 0.32 in (8mm)
Terminal torque:	Power: 15 lb-in (1.7 Nm) Control: 15 lb-in (1.7 Nm)
Mounting Hwd.:	35mm DIN Rail, #8 screw

Specification:

Description	TeSys D IEC Contactor - 25A - Vac Coil																		
Type	TeSys D IEC Contactor - 25A - 220Vac Coil																		
Voltages Code:	M7 at 220Vac 50/60 Hz																		
Coil Consumption:	Inrush 70 VA Sealed 7.5 VA																		
<table><tr><th colspan="2">Single Phase</th><th colspan="4">Three Phase</th></tr><tr><td>115V</td><td>230V</td><td>200V</td><td>230V</td><td>460V</td><td>575V</td></tr><tr><td>2 HP</td><td>3 HP</td><td>7.5 HP</td><td>7.5 HP</td><td>15 HP</td><td>20 HP</td></tr></table>		Single Phase		Three Phase				115V	230V	200V	230V	460V	575V	2 HP	3 HP	7.5 HP	7.5 HP	15 HP	20 HP
Single Phase		Three Phase																	
115V	230V	200V	230V	460V	575V														
2 HP	3 HP	7.5 HP	7.5 HP	15 HP	20 HP														