

SU816D150C

Meter mains, Homeline, combination service entrance, ringed socket, 150A, surface mount, maximum 8 spaces, 16 circuits, no bypass



Main

| | |
|---------------------------|-------------|
| Product or component type | Meter Mains |
| Range of product | Homeline |

Complementary

| | |
|---------------------------|---|
| Line Rated Current | 150 A |
| Short-circuit current | 22 kA |
| Network number of phases | 1 |
| Meter socket type | Ringed |
| Mounting | Surface |
| Number of spaces | 8 |
| Number of circuits | 16 |
| Number of Tandem Breakers | 8 |
| Hub type | A-L A |
| Electrical connection | Lugs line side Feed-thru lugs service ground Feed-thru lugs load side |
| Wire Size | AWG 6...300 kcmil aluminium/copper)line side AWG 14...AWG 1/0 aluminium/copper)load side AWG 14...AWG 1/0 aluminium/copper)service ground |
| Disconnect | Service disconnect (factory installed) |
| Main Breaker Rating | 150 A |
| Branch Breaker Rating | 100 A |
| Service feed location | OH UG |
| Bypass type | No bypass |
| Height | 34.00 in (863.60 mm) |
| Width | 14.95 in (379.73 mm) |
| Depth | 7.12 in (180.85 mm) |

Environment

| | |
|------------------------|-----------|
| Product certifications | UL E-6294 |
|------------------------|-----------|

Ordering and shipping details

| | |
|---------------------|--------------------------|
| Category | 00048-HOM METER MAINS |
| Discount Schedule | DE3A |
| GTIN | 00785901957706 |
| Package weight(Lbs) | 53.00 lb(US) (24.040 kg) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------|----------------------|
| Package 1 Height | 33.20 in (84.328 cm) |
| Package 1 width | 7.50 in (19.050 cm) |
| Package 1 Length | 15.40 in (39.116 cm) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|