



Note:  
- Drawings Not To Scale  
- Drawings Subject to Change Without Notice  
- Dimensions are inches next to [Millimeters]

Part No.:  
**LC1D326BD**

**Schneider Electric**  
Schneider Electric United States  
North American Division  
Boston One Campus  
800 Federal Street  
Andover, MA 01810, USA  
Phone: +1 8773425173  
Email: CCC@us.schneider-electric.com

Technical Information:  
Rating: 600V / 32A  
UL File/CCN: E164862 / NLDX  
CSA File: LR43364 3211 04  
Meets Standards: IEC 60647-4  
Weight: 0.83 lb (0.375 kg)  
Termination Method: Ring Tongue  
Wire Size: Power: Lug Size 0.32 in (8mm)  
Control: Lug Size 0.32 in (8mm)  
Terminal torque: Power: 15 lb-in (1.7 Nm)  
Control: 15 lb-in (1.7 Nm)  
Mounting Hwd.: 35mm DIN Rail, #8 screw

Description		Specification:			
Type		TeSys D IEC Contactor - 32A - Vdc Coil			
Voltages Code:		TeSys D IEC Contactor - 32A - 24Vdc Coil			
Coil Consumption:		BD at 24VDC			
		Inrush 5.4 W			
		Sealed 5.4 W			
		Single Phase		Three Phase	
115V	230V	200V	230V	460V	575V
2 HP	5 HP	10 HP	10 HP	20 HP	30 HP