UTH5203B METER SOCKET RINGLESS LEVER OH/UG 200A



Main Product or component type Meter Socket Hub type A ACP closing plate

Complementary

o o in promortically		
Meter socket rated current	200 A	
Number of jaws	5	
Bypass type	Lever bypass	
Phase	1 phase	
[Ue] rated operational voltage	<= 600 V AC	.!
Enclosure material	Steel	
Box number	8R	
Electrical connection	Lugs 0.5" hex	
Service feed location	OH UG	
Wiring configuration	3-wire	4
Device mounting	Surface	

Environment

Product certifications	UL Listed ANSI
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	00039 - METER SOCKETS & HUBS	
Discount Schedule	DE4	
GTIN	00785901861256	
Nbr. of units in pkg.	1	
Package weight(Lbs)	20.14 lb(US) (9.14 kg)	
Returnability	Yes	
Country of origin	US	

Packing Units

Package 1 Height	6.10 in (15.494 cm)
Package 1 width	11.60 in (29.464 cm)
Package 1 Length	19.80 in (50.292 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
EU RoHS Directive	Under investigation	
Contractual warranty		
Warranty	18 months	