



Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

LC1D150GD

Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone: +1 8773425173
Email: CCC@us.schneider-electric.com

Technical Information:

Rating:	600V / 150A
UL File/CCN:	E164862 / NLDX
CSA File:	LR43364 3211 04
Meets Standards:	IEC 60647-4
Weight:	2.5 lb (1.13 kg)
Termination Method:	Screw Clamp
Wire Size:	Power: #8 AWG - 250MCM
	Control: #14 - #18 AWG
Terminal torque:	Power: 100 lb-in (12 Nm)
	Control: 10 lb-in (1.2 Nm)
Mounting Hwd.:	2 x 35mm DIN Rail, M6 screw

Specification:

Description	TeSys D IEC Contactor - 150A - Vdc Coil
Type	TeSys D IEC Contactor - 150A - 125Vdc Coil
Voltages Code:	GD at 125Vdc
Coil Consumption:	Inrush 270 - 365 W
	Sealed 2.4 - 5.1 W

Single Phase			Three Phase		
115V	230V	200V	230V	460V	575V
N/A	N/A	40 HP	50 HP	100 HP	125 HP