

# Zelio Analog Interface Modules

Catalog

8501CT0502R07/13

2013

Class 8501



**Zelio Analog Interface Modules**  
**Table of Contents**

**Table of Contents**

Product Description.....5

    Measurement Signals for Thermocouples and Pt100 Probes .....5

    The Zelio Analog Range .....5

    Converters for J and K Type Thermocouples .....6

    Converters for Universal Pt100 Probes .....6

    Converters for Optimum Pt100 Probes .....6

    Universal Voltage/Current Converters .....7

    Description .....7

Specifications and Characteristics .....8

Selection .....10

Dimensions, Mounting Instructions, Wiring Diagrams.....12

Catalog Number Index .....13

## Product Description

The Zelio Analog range of converters is designed to convert signals emitted by sensors or electrical measurement devices, into standard electrical signals that are compatible with automation platforms and controllers (thermal processes, speed, etc.). They also allow the connection distance between a sensor and a measurement acquisition device to be increased, for example, between a thermocouple and a programmable controller.

These converters are suitable for universal use, as they are UL listed, CSA certified, and conform to IEC standards.

### Measurement Signals for Thermocouples and Pt100 Probes

The voltages induced by thermocouples vary between 10 and 80 mV/°C. Pt100 probes (100 ohms at 0 °C) produce about 0.5 mV/°C, with measurement currents of 1 mA. Depending on the sensor, the signal to be measured ranges from a few mV (thermocouple) to 250 and 700 mV for a Pt100 probe.

Therefore, it is difficult to transmit these low level signals over long electric lines without encountering problems of interference, signal reduction, or errors.

Connecting Zelio Analog converters close to the sensors resolves these problems:

- 4–20 mA current loops transmitted over a long distance are less sensitive to interference than low level voltage signals from sensors,
- signal reductions during transmission (resistance) of voltages do not occur, and
- the cables used to connect the converters to process equipment (programmable controllers) are standard cables, which are more cost effective than extension cables or compensation cables suitable for low level signals for Pt100 probes or thermocouples.

### The Zelio Analog Range

The Zelio Analog range was developed to work with most common applications and to ensure simplicity of installation:

- pre-set input and output scales, requiring no adjustment
- outputs protected against reverse polarity, overvoltage, and short-circuits
- 24 Vdc power supply
- sealable protective cover
- DIN rail mounting and screw mounting options
- LED indicator on the front panel
- input and output selector switches on the front panel
- output with fallback value if no input signal is present (due to failure of a sensor, for example)

The Zelio Analog converter range is divided into four families:

- Converters for J and K type thermocouples: **RMTJ/K**
- Converters for Universal Pt100 probes: **RMPT●0**
- Converters for Optimum Pt100 probes: **RMPT●3**
- Universal voltage/current converters: **RMC**

## Zelio Analog Interface Modules

### Product Description



RMTJ40BD



RMTK90BD



RMPT70BD

### Converters for J and K Type Thermocouples

Thermocouples, which consist of two metals with different thermoelectric characteristics, produce a voltage that varies according to temperature. This voltage is transmitted to the Zelio Analog converter, which converts it to a standard signal.

Converters for thermocouples have cold junction compensation to allow detection of measurement errors induced by the connection to the device itself.

Converters for J and K type thermocouples have:

- for inputs, a pre-set temperature range, depending on the model:
  - Type J: 32–302 °F (0–150 °C), 32–572 °F (0–300 °C), 32–1112 °F (0–600 °C)
  - Type K: 32–1112 °F (0–600 °C), 32–2192 °F (0–1200 °C)
- for outputs, a switchable signal: 0–10 V, 0–20 mA, and 4–20 mA

### Converters for Universal Pt100 Probes

Pt100 probes with platinum resistors are electrical conductors whose resistance varies according to the temperature. This ohmic resistance is transmitted to the Zelio Analog converter, which converts it to a standard signal.

Converters for Universal Pt100 probes have:

- for inputs, a pre-set temperature range, depending on the model:
  - -148–212 °F (-100 to 100 °C)
  - -40–104 °F (-40 to 40 °C)
  - 32–212 °F (0 to 100 °C)
  - 32–482 °F (0 to 250 °C)
  - 32–932 °F (0 to 500 °C)
- for outputs, a switchable signal: 0–10 V, 0–20 mA, and 4–20 mA

The products in the Universal Pt100 family allow wiring of Pt100 probes in 2, 3, and 4-wire mode.

### Converters for Optimum Pt100 Probes

Derived from the above family, these converters have:

- for inputs, a pre-set temperature range identical to that of converters for Universal Pt100 probes
- for outputs, 0–10 V signal dedicated to Zelio Logic analog inputs

They allow Pt100 probes to be wired in 2, 3, and 4-wire mode.

# Zelio Analog Interface Modules Product Description

## Universal Voltage/Current Converters

This family of converters allows the adaptation of electrical values (voltage/current). Four products are available:

- a cost effective converter which will convert a 0–10 V signal to a 4–20 mA signal, or vice versa,
- a Universal voltage/current converter allowing the most common signals. They have:
  - for inputs, a voltage/current range: 0–10 V,  $\pm 10$  V, 0–20 mA, and 4–20 mA
  - for outputs, a switchable voltage/current range: 0–10 V,  $\pm 10$  V, 0–20 mA, and 4–20 mA
- two Universal voltage/current converters which allow conversion of electrical power signals, both AC and DC

They have the following, depending on the model:

- **for voltage inputs**, a range of 0–500 V (AC or DC)
- for outputs, a switchable voltage/current range: 0–10 V, 0–20 mA, and 4–20 mA
- **for current inputs**, a range of 0–15 A (AC or DC)
- for outputs, a voltage/current range: 0–10 V, 0–20 mA, and 4–20 mA


## Description

Zelio Analog converters have the following on their front panel, depending on the model:

1. Two terminals for 24 Vdc supply connection
2. A “Power ON” LED
3. Three input selector switches (depending on model)
4. An output selector switch (depending on model)
5. A sealable protective cover
6. A screw terminal block for inputs
7. A screw terminal block for outputs



RMCA61BD



RMCL55BD

# Zelio Analog Interface Modules

## Specifications and Characteristics

## Specifications and Characteristics

### Environmental Characteristics

<b>Converter Types</b>		<b>RMTJ/K●●●●, RMP●●●●, RMC●●●●</b>
<b>Conforming to Standards</b>		IEC 60947-1, IEC 60584-1 (IEC 60751, DIN 43760 for RMP●●●●)
<b>Product Certifications</b>		UL Listed, File E164353 NKCR; CSA Certified, File 089150_S_000, Class 3211-07; <b>CE</b> ; GL
<b>Degree of Protection</b>	Housing	IP 50
	Terminal block	IP 20
<b>Flame Resistance</b>		1562 °F (850 °C) conforming to IEC 60695-2-1; conforming to UL 94
<b>Shock Resistance</b>		50 gn/11 ms conforming to IEC 68-2-27
<b>Vibration Resistance</b>		5 gn (10–100 Hz) conforming to IEC 68-2-6
<b>Immunity to EMC</b>	Resistance to electrostatic discharge	Level 3: 8 kV (air), 6 kV (contact) conforming to IEC 61000-4-2
	Immunity to fast transient currents	On the power supply: 2 kV; on the input-output: 1 kV conforming to IEC 61004-4
	Surge withstand	0.5 kV—waves 1.2/50 µs; 0.5 J conforming to IEC 61000-4-5
<b>Disturbance</b>	Radiated/conducted	CISPR11 and CISPR22 Group 1- Class B
<b>Rated Impulse Voltage (Conforming to IEC 60664-1)</b>		0.5 kV
<b>Ambient Air Temperature Around the Device</b>	Storage	-40–185 °F (-40–85 °C)
	Operation	Mounted side-by-side: 32–122 °F (0–50 °C); 2 cm spacing: 32–140 °F (0–60 °C)
<b>Degree of Pollution</b>		2 conforming to IEC 60664-1
<b>Mounting</b>		35 mm DIN rail, clip-on, or mounted directly to a panel
<b>Connection</b>		2-16 AWG or 1-14 AWG wire (2 x 1.5 mm <sup>2</sup> or 1 x 2.5 mm <sup>2</sup> cable)
<b>Tightening Torque</b>		5.3–9.8 lbf-in (0.6–1.1 Nm)

### Specific Characteristics

<b>Types of converter for thermocouples</b>		<b>RMTJ40BD</b>	<b>RMTJ60BD</b>	<b>RMTJ80BD</b>	<b>RMTK80BD</b>	<b>RMTK90BD</b>
<b>Input Types</b>	Thermocouple type to IEC 60584	J (Fe-CuNi)			K (Ni-CrNi)	
	Temperature range	32–302 °F 0–150 °C	32–572 °F 0–300 °C	32–1112 °F 0–600 °C	32–1112 °F 0–600 °C	32–2192 °F 0–1200 °C
<b>Analog Output (switchable to voltage or current)</b>						
<b>Voltage</b>	Range	0–10 V				
	Minimum impedance of load	100 kΩ				
<b>Current</b>	Range	0–20 mA; 4–20 mA				
	Maximum impedance of load	500 Ω				
<b>Built-in protection</b>		Reverse polarity, Overvoltage (± 30 V) and Short-circuit				
<b>Diagnostics</b>	Output state when no inputs are wired or when input wire broken	Output predetermined according to type of output selected: voltage = - 13 V current = 0 mA				
<b>Supply</b>						
<b>Voltage</b>	Rated	24 Vdc ± 20%, non-isolated				
<b>Maximum current consumption</b>	For voltage output	40 mA				
	For current output	60 mA				
<b>Built-in protection</b>		Reverse polarity				
<b>Signalling</b>		Green LED (power on)				
<b>Measurements</b>						
<b>Accuracy</b>	At 68 °F (20 °C)	± 1% of the full scale value ± 10% of the full-scale value (in an environment subject to electromagnetic interference of 10 V/m)				
	At 68 °F (20 °C) At 140 °F (60 °C)	± 0.25% of the full scale value ± 0.8% of the full scale value				
<b>Temperature coefficient</b>		200 ppm/°C (0.02%)				
<b>Cold junction compensation</b>		Built-in, cold junction measurement: 0–140 °F (0 to 60 °C)				

# Zelio Analog Interface Modules Specifications and Characteristics

## Specific Characteristics (continued)

Converter for Pt100 Probes		RMPT10/13BD	RMPT20/23BD	RMPT30/33BD	RMPT50/53BD	RMPT70/73BD
Input Types	Probe type	Pt100 - IEC 60751; DIN 43760 (2, 3, 4-wire)				
	Temperature range	- 40–104 °F - 40–40 °C	- 148–212 °F - 100–100 °C	32–212 °F 0–100 °C	32–482 °F 0–250 °C	32–932 °F 0–500 °C
Analog Output						
Output selection		0–10 V/0–20 mA, 4–20 mA switchable for RMP•T0BD 0–10 V or 4–20 mA for RMPT•3BD				
Voltage	Minimum impedance of load	100 kW				
Current	Maximum impedance of load	500 W / 100 kohms / 500 ohms				
Built-in protection		Reverse polarity, Overvoltage (± 30 V), and Short-circuit				
Diagnostics	Output state when no inputs are wired or when input wire broken	Output predetermined according to type of output selected: voltage = - 13 V current = 0 mA				
Supply						
Voltage	Rated	24 Vdc ± 20%, non-isolated				
Maximum current consumption	For voltage output	40 mA				
	For current output	60 mA				
Built-in protection		Reverse polarity				
Signalling		Green LED (power on)				
Measurements						
Accuracy	At 68 °F (20 °C)	± 0.5% (3 and 4-wire connection) of the full scale value ± 1% (2-wire connection) of the full scale value ± 10% of the full-scale value (in an environment subject to electromagnetic interference of 10 V/m)				
	At 140 °F (60 °C)	± 0.6% of the full scale value				
Repeat accuracy	At 68 °F (20 °C)	± 0.2% of the full scale value				
Temperature coefficient		150 ppm/°C (0.015 %)				
Connection in 2-wire mode						
Maximum resistance of cable		200 mW				
Voltage/Current Converters		RMCN22BD	RMCL55BD	RMCV60BD	RMCA61BD	
Input Types	Voltage	0–10 Vdc	0–10, ±10 Vdc	0–50; 0–300; 0–500 DC or AC 50/60 Hz	–	
	Current	4–20 mA	0–20 mA; 4–20 mA	–	–	
		–	–	–	0–1.5; 0–5; 0–15 A AC or DC, 50/60 Hz	
Analog Output						
Output selection		By wiring	Switchable	Switchable	By wiring	
Voltage	Range	0–10 V	0–10 V; ± 10	0–10 V	0–10 V	
	Minimum impedance of load	100 kW				
Current	Range	4–20 mA	0–20 mA; 4–20 mA	0–20 mA; 4–20 mA	0–20 mA; 4–20 mA	
	Maximum impedance of load	500 W				
Built-in protection		Reverse polarity, overvoltage (± 30 V) and short-circuit				
		Output predetermined according to type of output selected:				
Diagnostics	Output state when no inputs are wired or when input wire broken	voltage: < 0 V	voltage: - 10–10 V: -10 V 0–10 V: 0 V	voltage: < 0 V		
		current: < 4 mA	current: 0–20 mA: 0 mA 4–20 mA: 4 mA	current: 0–20 mA: 0 mA 4–20 mA: < 4 mA		
Supply						
Voltage	Rated	24 Vdc ± 20% non-isolated	24 Vdc ± 20% isolated (1.5 kV)			
Maximum current consumption	For voltage output	40 mA	70 mA			
	For current output	60 mA	90 mA			
Built-in protection		Reverse polarity				
Signalling		Green LED (power on)				
Measurements						
Accuracy	At 68 °F (20 °C)	± 1% of the full scale value ± 10% of the full-scale value (in an environment subject to electromagnetic interference of 10 V/m)			± 5% of the full scale value ± 10% of the full-scale value (in an environment subject to electromagnetic interference of 10 V/m)	
	At 140 °F (60 °C)	± 0.6% of the full scale value				
Repeat accuracy	At 68 °F (20 °C)	± 0.2% of the full scale value				
Temperature coefficient		200 ppm/°C (0.02 %)				0–1.5 A: 500 ppm/°C (0.05 %) 0–5 A: 1000 ppm/°C (0.1 %) 0–15 A: 2000 ppm/°C (0.2 %)

# Zelio Analog Interface Modules Selection

## Selection

Converters for J and K Type Thermocouples—Supply voltage 24 Vdc ± 20%, non-isolated

Type	Temperature Range		Switchable Output Signals	Catalog Number	Weight	
	°F	°C			lb	kg
Type J	32–302	0–150	0–10 V, 0–20 mA, 4–20 mA	RMTJ40BD	0.264	0.120
	32–572	0–300	0–10 V, 0–20 mA, 4–20 mA	RMTJ60BD	0.264	0.120
	32–1112	0–600	0–10 V, 0–20 mA, 4–20 mA	RMTJ80BD	0.264	0.120
Type K	32–1112	0–600	0–10 V, 0–20 mA, 4–20 mA	RMTK80BD	0.264	0.120
	32–2192	0–1200	0–10 V, 0–20 mA, 4–20 mA	RMTK90BD	0.264	0.120



RMTJ40BD



RMTK90BD

Converters for Universal Pt100 Probes—Supply voltage 24 Vdc ± 20%, non-isolated

Type	Temperature Range		Switchable Output Signals	Catalog Number	Weight	
	°F	°C			lb	kg
Pt100 2-wire, 3-wire, and 4-wire	- 40–104	- 40–40	0–10 V, 0–20 mA, 4–20 mA	RMPT10BD	0.264	0.120
	- 148–212	- 100–100	0–10 V, 0–20 mA, 4–20 mA	RMPT20BD	0.264	0.120
	32–212	0–100	0–10 V, 0–20 mA, 4–20 mA	RMPT30BD	0.264	0.120
	32–482	0–250	0–10 V, 0–20 mA, 4–20 mA	RMPT50BD	0.264	0.120
	32–932	0–500	0–10 V, 0–20 mA, 4–20 mA	RMPT70BD	0.264	0.120



RMPT70BD

Converters for Optimum Pt100 Probes (1)—Supply voltage 24 Vdc ± 20%, non-isolated

Type	Temperature Range		Switchable Output Signals	Catalog Number	Weight	
	°F	°C			lb	kg
Pt100 2-wire, 3-wire, and 4-wire	- 40–104	- 40–40	0–10 V or 4–20 mA	RMPT13BD	0.264	0.120
	- 148–212	- 100–100	0–10 V or 4–20 mA	RMPT23BD	0.264	0.120
	32–212	0–100	0–10 V or 4–20 mA	RMPT33BD	0.264	0.120
	32–482	0–250	0–10 V or 4–20 mA	RMPT53BD	0.264	0.120
	32–932	0–500	0–10 V or 4–20 mA	RMPT73BD	0.264	0.120

(1) Converters dedicated to Zelio Logic smart relays



RMPT13BD



## Zelio Analog Interface Modules Selection

### Universal Voltage/Current Converters

Type	Input signal	Output signal	Catalog Number	Weight	
				lb	kg
Supply voltage 24 Vdc $\pm$ 20%, non-isolated	0–10 V or 4–20 mA	0–10 V or 4–20 mA	<b>RMCN22BD</b>	0.264	0.120
Supply voltage 24 Vdc $\pm$ 20%, isolated	0–10 V, $\pm$ 10 V, 0–20 mA, 4–20 mA	Switchable: 0–10 V, $\pm$ 10 V, 0–20 mA, 4–20 mA	<b>RMCL55BD</b>	0.264	0.120
	0–50 V, 0–300 V, 0–500 V DC or AC, 50/60 Hz	Switchable: 0–10 V, 0–20 mA, 4–20 mA	<b>RMCV60BD</b>	0.264	0.120
	0–1.5 A, 0–5 A, 0–15 A DC or AC, 50/60 Hz	0–10 V, 0–20 mA, 4–20 mA	<b>RMCA61BD</b>	0.264	0.120



RMCN22BD



RMCL55BD



RMCA61BD

### Connection Accessories


Description	Type	Sold in lots of	Catalog Number	Weight	
				oz	g
Terminal blocks for connection of protective ground conductor	Screw	100	<b>NSYTRV62PE</b>	0.88	25.0
	Spring	100	<b>NSYTRV43PE</b>	0.52	14.7

# Zelio Analog Interface Modules

## Dimensions, Mounting Instructions, Wiring Diagrams


## Dimensions, Mounting Instructions, Wiring Diagrams

### Dimensions, Mounting Instructions




(1) Terminal block **AB1 RRTP435U** or **AB1 RRTP435U2**

### DIN Rail Mounting **AM1•••••**




### Panel mounting




Dimensions = In. (mm)

### Wiring Diagrams


#### RMTJ•••••, RMTK•••••



#### RMPT•0BD




#### RMPT•3BD




(1) Use one output only.

#### Input connections on RMPT•••••


2-wire type  
 $RL1 + RL2 \leq 200 \Omega$





3-wire type  
 $RL1 = RL2 = RL3$ ;  $RL1 + RL2 \leq 200 \Omega$




4-wire type  
 $RL1 + RL2 \leq 200 \Omega$



#### RMCN22BD




#### RMCL55BD




(1) Use one input only.

#### RMCV60BD



(1) Use one input only.

#### RMCA61BD



(1) Use one input only.  
 (2) Use one output only.



The input, output, and power supply lines must be kept away from the power cables to avoid effects due to induced interference.

The input and output cables must be shielded as indicated in the wiring diagrams and must be kept away from each other.

## Catalog Number Index

<b>Module .....</b>	<b>Page</b>
RMTJ40BD .....	8
RMTJ60BD .....	8
RMTJ80BD .....	8
RMTK80BD .....	8
RMTK90BD .....	8
RMPT10BD .....	8
RMPT20BD .....	8
RMPT30BD .....	8
RMPT50BD .....	8
RMPT70BD .....	8
RMPT13BD .....	8
RMPT23BD .....	8
RMPT33BD .....	8
RMPT53BD .....	8
RMPT73BD .....	8
RMCL55BD .....	9
RMCN22BD .....	9
RMCV60BD .....	9
RMCA61BD .....	9
NSYTRV62PE .....	9
NSYTRV42PE .....	9

**Schneider Electric USA, Inc.**

1415 S. Roselle Road  
Palatine, IL 60067 USA  
1-888-778-2733  
[www.schneider-electric.us](http://www.schneider-electric.us)

© 2006–2013 Schneider Electric All Rights Reserved

Zelio and Schneider Electric are trademarks owned by Schneider Electric Industries SAS or its affiliated companies. All other trademarks are the property of their respective owners.

8501CT0502R07/13 Replaces 8501CT0502, 02/2006