# Product data sheet Characteristics

# RC816F200SS

Meter mains, Homeline, combination service entrance, ringless socket, 200A, outdoor surface mount, maximum 8 spaces, 16 circuits, no bypass





Main	
Product or component type	Meter Mains
Range of product	Homeline
Includes	Circuit-breaker 1) 2P 200 A 120/240 V AC main supply ready assembled

#### Complementary

Line Rated Current	200 A	
Short-circuit current	22 kA	
Network number of phases	1	
Meter socket type	Ringless	
Mounting	Surface outdoor)	
Number of spaces	8	
Number of circuits	16	
Number of Tandem Breakers	8	
Hub type	A	
Electrical connection	Feed-thru lugs service ground Feed-thru lugs line side	
Wire Size	AWG 8AWG 2/0 aluminium/copper)service ground AWG 6350 kcmil aluminium/copper)line side	
Tightening torque	Main lugs 250 lb.in, AWG 6350 kcmil, aluminium/copper Service ground 50 lb.in, AWG 14AWG 2/0, copper Service ground 50 lb.in, AWG 12AWG 2/0, aluminium Branch lugs 35 lb.in, AWG 6AWG 4, aluminium/copper Branch lugs 25 lb.in, AWG 8, aluminium/copper Branch lugs 20 lb.in, AWG 14AWG 10, copper Branch lugs 20 lb.in, AWG 12AWG 10, aluminium Cover 10 lb.in	
Disconnect	Service disconnect (factory installed)	
Main Breaker Rating	200 A	
Branch Breaker Rating	200 A	
Service feed location	OH UG	
Bypass type	No bypass	
Height	41.16 in (1045.46 mm)	
Width	18.76 in (476.50 mm)	
Depth	5.41 in (137.41 mm)	

#### Environment

Product certifications	UL E-6294	

# Ordering and shipping details

Category	00048 - HOM METER MAINS
Discount Schedule	DE3A
GTIN	00785901946601
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

### Packing Units

Package 1 Height	0.44 ft (0.135 m)
Package 1 width	1.53 ft (0.467 m)
Package 1 Length	3.41 ft (1.039 m)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

#### Contractual warranty

Warranty	18 months