



Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
LC1D32Q7

Schneider Electric
Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone: +1 8773425173
Email: CCC@us.schneider-electric.com

Technical Information:
Rating: 600V / 32A
UL File/CCN: E164862 / NLDX
CSA File: LR43364 3211 04
Meets Standards: IEC 60647-4
Weight: 0.83 lb (0.375 kg)
Termination Method: Screw Clamp
Wire Size: Power: #6 - #14 AWG
Control: #10 - #18 AWG
Terminal torque: Power: 20 lb-in (2.5 Nm)
Control: 15 lb-in (1.7 Nm)
Mounting Hwd.: 35mm DIN Rail, #8 screw

Specification:

| | |
|----------------|---|
| Description | TeSys D IEC Contactor - 32A - Vac Coil |
| Type | TeSys D IEC Contactor - 32A - 380Vac Coil |
| Voltages Code: | Q7 at 380Vac 50/60 Hz |

Coil Consumption: Inrush 70 VA
Sealed 7.5 VA

| Single Phase | | Three Phase | | | |
|--------------|------|-------------|-------|-------|-------|
| 115V | 230V | 200V | 230V | 460V | 575V |
| 2 HP | 5 HP | 10 HP | 10 HP | 20 HP | 30 HP |