



Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
LC1D40A6G7

Schneider Electric
Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone: +1 8773425173
Email: CCC@us.schneider-electric.com

| Technical Information: | |
|------------------------|-----------------------------------------------------|
| Rating: | 600V / 40A |
| UL File/CCN: | E164862 / NLDX |
| CSA File: | LR43364 3211 04 |
| Meets Standards: | IEC 60647-4 |
| Weight: | 2.28 lb (0.850 kg) |
| Termination Method: | Ring Tongue |
| Wire Size: | Power: See Chart Control: #12 - #18 AWG |
| Terminal torque: | Power: 54 lb-in (6 Nm) Control: 8 lb-in (0.9 Nm) |
| Mounting Hwd.: | 35mm DIN Rail, #8 screw |

Specification:

| Description | TeSys D IEC Contactor New Type with Everlink® - 40A - Vac Coil | | | | | | | | | | | | | | | | | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|--------------|-------|-------------|-------|--|--|------|------|------|------|------|------|------|------|-------|-------|-------|-------|
| Type | TeSys D IEC Contactor - 40A - 120Vac Coil | | | | | | | | | | | | | | | | | | |
| Voltages Code: | G7 at 120Vac 50/60 Hz | | | | | | | | | | | | | | | | | | |
| Coil Consumption: | Inrush 160 VA Sealed 15 VA | | | | | | | | | | | | | | | | | | |
| <table><tr><th colspan="2">Single Phase</th><th colspan="4">Three Phase</th></tr><tr><td>115V</td><td>230V</td><td>200V</td><td>230V</td><td>460V</td><td>575V</td></tr><tr><td>3 HP</td><td>5 HP</td><td>10 HP</td><td>10 HP</td><td>30 HP</td><td>30 HP</td></tr></table> | | Single Phase | | Three Phase | | | | 115V | 230V | 200V | 230V | 460V | 575V | 3 HP | 5 HP | 10 HP | 10 HP | 30 HP | 30 HP |
| Single Phase | | Three Phase | | | | | | | | | | | | | | | | | |
| 115V | 230V | 200V | 230V | 460V | 575V | | | | | | | | | | | | | | |
| 3 HP | 5 HP | 10 HP | 10 HP | 30 HP | 30 HP | | | | | | | | | | | | | | |