8536SCH3V02H30S

NEMA Motor Starter, Type S, nonreversing, Size 1, 27A, 10 HP at 460 VAC, up to 100 kA SCCR, 3 phase, 3 pole, Motor Logic, 120 VAC coil, NEMA 3R



Main Product Type Motor starter

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

1	
27 A	
3P	
600 V AC	
3 phase	
Solid state Motor Logic class 10/20	
7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC	
Circuit-breaker 70 A maximum: 100 kA at 480 V AC Fuse J 60 A maximum: 100 kA at 600 V AC Fuse T 60 A maximum: 100 kA at 600 V AC Fuse RK1 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 A maximum: 100 kA at 600 V AC	
110 V AC 50 Hz 120 V AC 60 Hz	
Separate control circuit	
No control units	
Without pilot light	
Without	
1 fuse	
Screw clamp terminals	
12.28 in (311.91 mm)	
8.84 in (224.54 mm)	
7.13 in (181.10 mm)	
	27 A 3P 600 V AC 3 phase Solid state Motor Logic class 10/20 7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC Circuit-breaker 70 A maximum: 100 kA at 480 V AC Fuse J 60 A maximum: 100 kA at 600 V AC Fuse RK1 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 A maximum: 100 kA at 600 V AC Suse RK5 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 Hz 110 V AC 50 Hz 120 V AC 60 Hz Separate control circuit No control units Without pilot light Without 1 fuse Screw clamp terminals 12.28 in (311.91 mm) 8.84 in (224.54 mm)

Environment

Enclosure Type	NEMA 3R painted sheet steel
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901340430
Nbr. of units in pkg.	1
Package weight(Lbs)	26.72 lb(US) (12.12 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	12.28 in (31.2 cm)	
Package 1 width	8.86 in (22.5 cm)	
Package 1 Length	7.13 in (18.1 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months