Product data sheet Characteristics

LE1D128B62OG70 FULL-VOLTAGE NON-REVERSING IEC STARTER FUSIBLE DISCONNECT 30A TYPE 1



Main	
Product or Component Type	Full voltage starter
Range of product	Instakits
Starter Type	Non reversing
Disconnect Type	Fusible disconnect

Complementary

Control Circuit Voltage	120 V AC 50/60 Hz	
Current Rating	12 A	
Horsepower Rating	0.5 Hp 120 V AC, 1 phase 2 Hp 240 V AC, 1 phase 3 Hp 208 V AC, 3 phase 3 Hp 230 V AC, 3 phase 7.5 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Auxiliary Contacts	1 NO + 1 NC	
Protection Type	Switch-disconnector fuse 30 A	
Location of connection	Line	

Environment

LITVITOTITICITE		
Product Certifications	CSA	
	IEC	
	UL	
Enclosure Type	NEMA 1 steel	

Ordering and shipping details

0 11 0		
Category	22313 - CTRS,D-LINE,ENCL (METAL)	
Discount Schedule	l11	
GTIN	00785901408208	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1 lb(US) (0.45 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Package 1 Height	11.10 in (28.194 cm)
Package 1 width	12.90 in (32.766 cm)
Package 1 Length	28.60 in (72.644 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

	•
Warranty	18 months