

Product data sheet

Characteristics

8903PBQ10BV02

panelboard lighting contactor, 100 AMP, 2 pole,
bus mount, 120V 60Hz coil



Main

Product	Mechanically Held Lighting Contactor
Type	PB
Control Circuit	Common control circuit

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	100 A
Number of Poles	2P
AWG gauge	AWG 1/0 aluminium/copper)power AWG 18...AWG 10 copper)control
Maximum Overall Voltage	600 V AC
Auxiliary contact composition	Without
Mounting support	busbar
Electrical Connection	Busbar connection
Height	8.31 in (211 mm)
Depth	3.39 in (86 mm)
Width	7.52 in (191 mm)

Environment

Product Certifications	UL Listed CSA
------------------------	------------------


Ordering and shipping details

Category	21323 - 8903 PB
Discount Schedule	CP1
GTIN	785901851554
Nbr. of units in pkg.	1
Package weight(Lbs)	7.00 lb(US) (3.175 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	8.31 in (21.1 cm)
Package 1 width	7.52 in (19.1 cm)
Package 1 Length	3.39 in (8.6 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------