

Main

Range	PowerLogic
Product or Component Type	Terminal block
Terminal block type	Shorting
Mounting Mode	By screws

Complementary

Length	4.50 in (114.3 mm)
Width	2.00 in (50.8 mm)
Height	1.25 in (31.8 mm)
Connections - terminals	6 x screw terminal upstream 6 x screw terminal downstream
Cable cross section	0.00...0.02 in ² (0.5...13.3 mm ²)
Tightening torque	19.91...20.00 lbf.in (2.25...2.26 N.m)
[Ue] rated operational voltage	600 V
Line Rated Current	60 A, AWG 22...AWG 6
Material	Base Noryl Base Nickel plated brass terminal
Flame retardance	V1 UL 94

Environment



Product Certifications	CSA UL
Ambient air temperature for operation	-4...221 °F (-20...105 °C)

Ordering and shipping details

Category	09756 - POWERLOGIC INTERMEDIATE ACCYS
Discount Schedule	PM1
GTIN	785901004547
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------