# **LE1D18F7**

# TeSys LE - enclosed DOL starter - 18 A - 110 V AC coil





Main	
Range	TeSys
Product name	TeSys LE
Device short name	LE1D
Product or Component Type	Enclosed DOL starter
Device Application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay ordered separately Contactor
Control type	Push-button start Green I

Push-button stop/reset Red O

#### Complementary

[Ith] Conventional free air thermal current	18 A AC-3	
Motor power kW	10 KW 500 V AC 50/60 Hz	
•	10 KW 660/690 V AC 50/60 Hz	
	4 KW 220/230 V AC 50/60 Hz	
	9 KW 415 V AC 50/60 Hz	
	9 KW 440 V AC 50/60 Hz	
	7.5 kW 380/400 V AC 50/60 Hz	
[Ith] Conventional free air thermal current	17 A	
[Uc] control circuit voltage	110 V AC 50/60 Hz	
Cable entry number	2 ISO20 top	
	2 ISO20 bottom	
	2 Pg 16 bottom	
	2 ISO25 top	
	2 Pg 21 bottom	
	2 ISO25 bottom	
Width	3.98 in (101 mm)	
Height	7.91 in (201 mm)	
Depth	6.04 in (153.5 mm)	
Product Weight	2.24 lb(US) (1.015 kg)	

#### Environment

Material	Polycarbonate
IP degree of protection	IP65 IEC 60529
IK degree of protection	IK07 IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	23104 °F (-540 °C)
Environmental characteristic	Standard environment

#### Ordering and shipping details

Category	22313 - CTRS,D-LINE,ENCL (METAL)	
Discount Schedule	l11	
GTIN	3389110578133	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.63 lb(US) (1.191 kg)	
Returnability	No	
Country of origin	FR	

### **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	6.50 in (16.5 cm)	
Package 1 width	7.80 in (19.8 cm)	
Package 1 Length	9.84 in (25 cm)	
Unit Type of Package 2	P06	
Number of Units in Package 2	22	
Package 2 Weight	86.42 lb(US) (39.2 kg)	
Package 2 Height	28.94 in (73.5 cm)	
Package 2 width	23.62 in (60 cm)	
Package 2 Length	31.50 in (80 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxic & Antimony trioxide, which is known to the State of California to cause cancer. more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

### Contractual warranty

Warranty	18 months	