


KNOCKOUTS		
SYMBOL	CONDUIT SIZE	
	IN	MM
A	.50	13
B	.75	19
D	1.25	32
E	1.50	38
F	2.00	51
G	2.50	64
H	3.00	76
I	3.50	89
J	4.00	102



ALTERNATE LUGS **

LUG MANUFACTURER	CATALOG NUMBER	WIRE RANGE AWG/kcmil	WIRE BENDING SCREW TORQUE LB-IN OR VERSA-CRIMP CRIMPING TOOL
ILSCO	TA-600-2N	2-600 CU/AL	375
	TA-800-2N	300-800 CU/AL	500
CONNECTOR MANUFACTURING COMPANY	A1B2-600-2	2-600 CU/AL	375
	L1D2-800	300-800 CU/AL	550
ANDERSON	L1D2-600	2-600 CU/AL	550
	L1D2-800	300-800 CU/AL	550
	VCEL-050-12H2	2/0-500 CU/AL	VC6-FT
	VCEL-060-12H2	400-600 AL OR 400-500 CU	VC6-FT
	VCEL-075-12H2	500-750 AL OR 500 CU	VC6-FT
	VACL-500-12BN	4/0-500 CU/AL	VC6-FT
	VACL-600-12BN	350-600 AL OR 350-500 CU	VC6-FT VC8
	VACL-750-12BN	500-750 AL OR 500 CU	VC6-FT VC8
	VHCL-500-12BN	4/0-500 CU/AL	VC6-FT VC7FT
	VHCL-600-12BN	250-600 CU	VC6-FT VC7FT VC8

** ALTERNATE LUGS REQUIRES USE OF LUG LANDING KIT PART NUMBER EZMSK2 (ORDER SEPARATELY).

DUAL DIMENSIONS: INCHES
MILLIMETERS

SYSTEM TYPE	MAIN RATING (AMPERES)	CATALOG NUMBER *	BUS BAR MATERIAL	LINE PHASE AND NEUTRAL LUG WIRE RANGE FOR AL OR CU CONDUCTORS (FACTORY INSTALLED)	GROUND LUG WIRE RANGE (FACTORY INSTALLED)
3Ø 4W 208Y/120VAC OR 240/120VAC DELTA	400	EZM3400TB	ALUMINUM	(2) 3/0-500	(1) #6-300
		EZM3400TBCU	COPPER		

*SERIES M04

NOTES:
FINISH - GRAY BAKED ENAMEL POWDER COAT PAINT OVER CLEANED GALVANNEALED STEEL.
UL LISTED - FILE-10582, VOL. M, E131840, VOL. M.
SUITABLE FOR USE ON THE LINE SIDE OF SERVICE EQUIPMENT.
MAIN HORIZONTAL CROSS BUS RATED AT 800 AMPERES.
MAIN DEVICES ARE SEALABLE BY UTILITY.
GANGABLE MULTI-METERING EQUIPMENT IS DESIGNED FOR WALL MOUNTING ONLY.
(NOT SUITABLE FOR FLOOR STANDING EQUIPMENT).

EZ METER-PAK GANGABLE
MULTI-METERING EQUIPMENT
400A 3PH 4W MAIN LUGS TERMINAL BOXES
OVERHEAD/UNDERGROUND FEED
RAINPROOF NEMA TYPE 3R ENCLOSURE

SQUARE D™
by Schneider Electric

DWG# 3368
NO.