



Main	
Range	Linergy
Range of product	Linergy
Product or Component Type	Device feeder
Product name	Linergy FM
Range compatibility	Prisma G enclosure Prisma P enclosure Prisma PH enclosure
Product Compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Mounting Support	Plain backplate
	DIN rail
	Slotted backplate
Installed device	Modular device
Poles description	3P
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[le] rated operational current	200 A
Line Rated Current	200 A 104 °F (40 °C)
[lpk] rated peak withstand current	20 kA
I²t on activation	6700000 A².s
Connections - terminals	Supply crimped lug0.08 in² (50 mm²)
	Supply flexible bars, 20 x 3 mm
	Distribution quick-connect terminal strips phase) , 12 x 0.010.02 in² (4 10 mm²) flexible)
	Distribution quick-connect terminal strips phase) , 12 x 0.010.02 in² (4 10 mm²) rigid)
	Distribution quick-connect terminal strips neutral) , 18 x 0.010.02 in² (4 10 mm²) flexible)
	Distribution quick-connect terminal strips neutral), 18 x 0.010.02 in² (4 10 mm²) rigid)
9 mm pitches	48
Total number of 18 mm modules	24
Product Weight	2.91 lb(US) (1.32 kg)
Color	Anthracite grey RAL 7016)

Environment

Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
Product Certifications	ASEFA

Ordering and shipping details

Category	01078-DE2 MISC	
Discount Schedule	DE2	
GTIN	3303430040132	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.82 lb(US) (1.28 kg)	
Returnability	No	
Country of origin	PL	

Packing Units

PCE
2.64 in (6.7 cm)
2.99 in (7.6 cm)
17.60 in (44.7 cm)
P06
120
349.21 lb(US) (158.4 kg)
38.19 in (97 cm)
31.50 in (80 cm)
23.62 in (60 cm)
BB1
5
14.13 lb(US) (6.41 kg)
2.64 in (6.7 cm)
14.80 in (37.6 cm)
17.60 in (44.7 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant [₫] EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------