



Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
LC1D50A6B7

Schneider Electric
Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone: +1 8773425173
Email: CCC@us.schneider-electric.com

Technical Information:	
Rating:	600V / 50A
UL File/CCN:	E164862 / NLDX
CSA File:	LR43364 3211 04
Meets Standards:	IEC 60647-4
Weight:	2.29 lb (0.855 kg)
Termination Method:	Ring Tongue
Wire Size:	Power: See Chart Control: #12 - #18 AWG
Terminal torque:	Power: 54 lb-in (6 Nm) Control: 8 lb-in (0.9 Nm)
Mounting Hwd.:	35mm DIN Rail, #8 screw

Specification:

Description	TeSys D IEC Contactor New Type with Everlink® - 50A - Vac Coil																		
Type	TeSys D IEC Contactor - 50A - 24Vac Coil																		
Voltages Code:	B7 at 24Vac 50/60 Hz																		
Coil Consumption:	Inrush 160 VA Sealed 15 VA																		
<table><tr><th colspan="2">Single Phase</th><th colspan="4">Three Phase</th></tr><tr><td>115V</td><td>230V</td><td>200V</td><td>230V</td><td>460V</td><td>575V</td></tr><tr><td>3 HP</td><td>7.5 HP</td><td>15 HP</td><td>15 HP</td><td>40 HP</td><td>40 HP</td></tr></table>		Single Phase		Three Phase				115V	230V	200V	230V	460V	575V	3 HP	7.5 HP	15 HP	15 HP	40 HP	40 HP
Single Phase		Three Phase																	
115V	230V	200V	230V	460V	575V														
3 HP	7.5 HP	15 HP	15 HP	40 HP	40 HP														