QO2125BNF

Load center enclosure, QO, 1 phase, 2 spaces, used with 125A breaker, NEMA1, flush cover, UL





Main

Mani	
Marketing Trade Name	QO
Product Type	Enclosure
Enclosure Type	Enclosure
Cover Type	Flush cover

Complementary

Complementary		
Tightening Torque	35 lb.in, AWG 14AWG 10, copper 35 lb.in, AWG 12AWG10, aluminium 40 lb.in, AWG 8AWG 4, aluminium/copper 50 lb.in, AWG 3AWG 2, aluminium/copper Main lugs 50 lb.in, AWG 3AWG 2/0, aluminium/copper	
Rated Current	125 A	
Number of Spaces	2	
Max Short Circuit Current Rating	22 kA	
Maximum Number of Single Pole Circuits	2	
Maximum Number of Tandem Breakers	0	
Number of Phases	1 phase	
Wire Size	AWG 12AWG 2/0 aluminium AWG 14AWG 2/0 copper	
Ground Bar	Grounding bar (ordered separately)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Busbar Material	Tin plated copper busbar	
Enclosure Material	Welded sheet steel	
Surface Finish	Baked enamel Gray	
Box Number	18	
Height	16.10 in (409 mm)	
Width	5.87 in (149 mm)	
Depth	12 in (304.80 mm)	

Environment

Enclosure Rating	NEMA 1 indoor
Product Certifications	UL Listed

Ordering and shipping details

Category	00005 - QO,Q2L 2P ENCL & BREAKERS
Discount Schedule	DE2A
GTIN	785901051787
Nbr. of units in pkg.	1
Package weight(Lbs)	6.95 lb(US) (3.152 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.90 in (9.906 cm)
Package 1 width	7.60 in (19.304 cm)
Package 1 Length	17.90 in (45.466 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months