

Main	
Range	PratiKa
Product or Component Type	Wander plug
Device short name	PratiKa plug
Plug, socket category	Extra-low voltage
Poles description	3P
Network type	AC
Outlet standard	Industrial

Complementary

Plug, socket, control station shape	Straight	
Line Rated Current	16 A	
[Ue] rated operational voltage	4050 V	
Network Frequency	50/60 Hz	
Secondary keyway clockwise position	12 h	
Plug, socket material	Housing self-extinguishing engineering polymer	
Contacts material	Pins nickel plated brass	
Connections - Terminals	Captive screws	
Cable cross section	0.010.02 in² (410 mm²)	
Cable outer diameter	0.240.91 in (623 mm)	
Cable entry	Cable gland	
Thread type	Pg 21	
Net Weight	0.41 lb(US) (0.184 kg)	
Height	5.71 in (145 mm)	
Width	2.81 in (71.5 mm)	
Depth	2.81 in (71.5 mm)	
Color	Gray RAL 7035)	
Voltage colour	White	

Environment

Standards	IEC 60309-1	
	IEC 60309-2	
IP degree of protection	IP67 conforming to IEC 60529	
IK degree of protection	IK08 EN 62262	
Fire resistance	1562 °F (850 °C) IEC 60695-2-11	
Relative humidity	50 % 104 °F (40 °C)	
	70 % 86 °F (30 °C)	
	90 % 68 °F (20 °C)	
Operating altitude	6561.68 ft (2000 m)	
Ambient air temperature for operation	95 °F (35 °C) 86400 s)	
	-13104 °F (-2540 °C)	

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	3303430823544
Nbr. of units in pkg.	1
Package weight(Lbs)	6.00 oz (170 g)
Returnability	Yes
Country of origin	US

Packing Units

· coming come	
Unit Type of Package 1	PCE
Package 1 Height	3.03 in (7.7 cm)
Package 1 width	3.03 in (7.7 cm)
Package 1 Length	5.47 in (13.9 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	4.03 lb(US) (1.828 kg)
Package 2 Height	4.65 in (11.8 cm)
Package 2 width	8.27 in (21 cm)
Package 2 Length	10.83 in (27.5 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	30
Package 3 Weight	13.16 lb(US) (5.971 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	[☑] China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
	— 1 Todact Entironment Tomo	

Contractual warranty

Contractal warranty		
Warranty	18 months	