170NEF11021

Modicon Momentum - Modbus Plus communication adaptor



Main

Range of Product	Modicon Momentum automation platform
Product or Component Type	Modbus Plus communication adaptor
Bus manager PLC	Compact 984 Quantum
Structure type	Industrial
Communication Port Protocol	Modbus Plus
Method of access	Peer to peer Token bus
Transmission Rate	1 Mbit/s
Transmission support medium	Twisted pair

Complementary

Topology	Multidrop, device connecting by extension or tap off cable
Number of devices per segment	031 per segment 063 all segment
Maximum cable distance between devices	16404.20 ft (5000 m) with repeater
Data format	984
Fail state	Full scale value Maintain value Fallback to zero Forcing to state zero
Supply	From I/O base
Marking	CE
Local signalling	For module powered up or communicating (MB + ACT) 1 LED (green) For communication error network A (ERR A) 1 LED (red) For communication error network B (ERR B) 1 LED (red)
Electrical connection	1 connector SUB-D 9 for connecting Modbus Plus network 1 connector SUB-D 9 for redundant Modbus Plus network

Environment

Environment		
Product Certifications	CSA	
	UL	
Protective treatment	TC	
Resistance to electrostatic discharge	4 KV contact IEC 801-2	
	8 kV on air IEC 801-2	
Resistance to electromagnetic fields	9.14 V/m (10 V/m) 801000 MHz IEC 801-3	
Ambient air temperature for operation	32140 °F (060 °C)	
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)	
Relative Humidity	95 % without condensation	
Operating altitude	<= 16404.2 ft (5000 m)	

Ordering and shipping details

Category	18206 - MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	3595861147362
Nbr. of units in pkg.	1
Package weight(Lbs)	6.81 oz (193 g)

Returnability	No
Country of origin	FR
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	2.28 in (5.8 cm)
Package 1 width	7.09 in (18 cm)
Package 1 Length	10.20 in (25.9 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	4.41 lb(US) (2 kg)
	11.81 in (30 cm)
Package 2 Height	(55 5)
	11.81 in (30 cm)
Package 2 Height Package 2 width Package 2 Length	<u> </u>
Package 2 width Package 2 Length Offer Sustainability California proposition 65	11.81 in (30 cm)
Package 2 width Package 2 Length Offer Sustainability California proposition 65	11.81 in (30 cm) 15.75 in (40 cm) WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to
Package 2 width Package 2 Length Offer Sustainability California proposition 65 REACh Regulation	11.81 in (30 cm) 15.75 in (40 cm) WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Package 2 width Package 2 Length Offer Sustainability California proposition 65 REACh Regulation EU RoHS Directive	11.81 in (30 cm) 15.75 in (40 cm) WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov REACh Declaration Pro-active compliance (Product out of EU RoHS legal scope)
Package 2 width Package 2 Length Offer Sustainability	11.81 in (30 cm) 15.75 in (40 cm) WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov Pro-active compliance (Product out of EU RoHS legal scope) For EU RoHS Declaration
Package 2 width Package 2 Length Offer Sustainability California proposition 65 REACh Regulation EU RoHS Directive Mercury free	11.81 in (30 cm) 15.75 in (40 cm) WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov REACh Declaration Pro-active compliance (Product out of EU RoHS legal scope) Let RoHS Declaration Yes

Warranty	18 months
•	