

Product data sheet

Characteristics

MA8IBA24

Surge protection module, Surgelogic, MA,
240kA, 600Y/347 VAC, 3 phase, 4 wire, SPD
type 2



Main

Product	Surge protection module
Range	Surgelogic
Device Short Name	IBA
Accessory Category	Replacement part

Complementary

Surge Current	240 kA per phase
Voltage Rating	600Y/347 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Connection	Terminals
MCOV	420 V
Nominal Discharge Current	20 kA
SCCR	200 kA
Local Signalling	Status LED green normal operation
Provided Equipment	Alarm enable/disable switch
Height	6.25 in (158.8 mm)
Width	9.92 in (252 mm)
Depth	2.69 in (68.3 mm)

Environment

Enclosure Rating	NEMA 2
Enclosure Material	Black Plastic
Standards	UL 1449:ed. 4 UL 1283:ed. 5 CSA C22.2 No 8:1986 ANSI/IEEE C62.41 ANSI/IEEE C62.45 NEC 285
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08467-SURGE PROTECTION REPLACEMENT
Discount Schedule	DE1B
GTIN	785901293613
Nbr. of units in pkg.	1
Package weight(Lbs)	9.40 lb(US) (4.264 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.80 in (19.812 cm)
Package 1 width	9.30 in (23.622 cm)
Package 1 Length	12.50 in (31.75 cm)

Contractual warranty

Warranty	18 months
----------	-----------