



(HUBBLELOCK RECEPTACLE)

WIRING DIAGRAMS	
FUSIBLE	NOT FUSIBLE

TERMINAL LUGS ‡			
AMPERES	MAX. WIRE	MIN. WIRE	TYPE
60	# 2 AWG	# 12 AWG	AL
	# 2 AWG	# 12 AWG	CU

KNOCKOUTS				
SYMBOL	CONDUIT SIZE		DIAMETER	
	IN	MM	IN	MM
A	.50	13	.88	22
B	.75	19	1.13	29
C	1.00	25	1.38	35
D	1.25	32	1.75	45
E	1.50	38	2.00	51
F	2.00	51	2.50	64

DUAL DIMENSIONS, INCHES  
MILLIMETERS

NOTES:  
FINISH: SWITCHES - GRAY BAKED ENAMEL  
HUBBLELOCK RECEPTACLE - CADMIUM PLATED  
UL LISTED - FILE E-2875  
SHORT CIRCUIT CURRENT RATINGS:  
10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES.  
WHEN MOUNTING THESE SWITCHES, ALLOW 4.00 IN / 102 MM MIN. CLEARANCE  
BETWEEN ENCLOSURES FOR OPENING OF SIDE HINGED DOOR.  
‡ LUGS SUITABLE FOR 60°C OR 75°C COPPER OR ALUMINUM CONDUCTORS.

CATALOG NUMBER	VOLTAGE RATINGS	AMPERE RATING	WIRING DIAG.	HORSEPOWER RATINGS								
				240VAC		480VAC				600VAC		
				MAX.		STD.		MAX.		STD.		
				1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	3Ø	1Ø	3Ø
H362WH HU362WH	600VAC 600VAC	60 60	A B	- 10	- 20	5 -	15 -	20 25	30 50	15 -	- 30	50 60

HEAVY DUTY SAFETY SWITCHES  
WITH RECEPTACLE  
60 AMPERES  
ENCLOSURE - NEMA TYPE 1 GENERAL PURPOSE

**SQUARE D COMPANY**

DWG. NO. 1944