

| Main | | |
|------------------------------|-------------------------------|--|
| Product or Component Type | Shunt trip | |
| Circuit breaker type | H-frame J-frame L-Frame | |

Complementary

| Rated voltage | 24 V AC |
|-------------------|--|
| Tightening torque | 12.39 lbf.in (1.4 N.m) 0.000.00 in² (0.822.5 mm²) (AWG 18AWG 14) |

Environment

| Product certifications | CSA |
|------------------------|-----|
| | |

Ordering and shipping details

| er dering dire emplang detaile | |
|--------------------------------|---|
| Category | 01103-H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES |
| Discount Schedule | DE2 |
| GTIN | 785901467595 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 4.64 oz (131.542 g) |
| Returnability | Yes |
| Country of origin | US |
| | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------|--------------------|--|
| Package 1 Height | 1.40 in (3.556 cm) | |
| Package 1 width | 2.50 in (6.35 cm) | |
| Package 1 Length | 3.20 in (8.128 cm) | |

Offer Sustainability

| Onor Guotamability | | |
|----------------------------|--------------------------------|--|
| REACh Regulation | REACh Declaration | |
| EU RoHS Directive | Compliant EEU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | ₽¥Yes | |
| China RoHS Regulation | ☑ China RoHS Declaration | |
| | | |

Contractual warranty

| | • | |
|----------|-----------|--|
| Warranty | 18 months | |