



TERMINAL LUGS ‡			
AMPERES	MAX. WIRE	MIN. WIRE	TYPE
30	# 6 AWG	# 12 AWG	AL
30	# 6 AWG	# 14 AWG	CU

NOTES:
 FINISH: SWITCHES - GRAY BAKED ENAMEL
 CROUSE-HINDS RECEPTACLE - CAST ALUMINUM
 UL LISTED - FILE E-2875
 CSA CERTIFIED
 SHORT CIRCUIT CURRENT RATINGS:
 10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES.
 200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R OR J FUSES.
 WHEN MOUNTING THESE SWITCHES, ALLOW 4.00 IN / 102 MM MIN. CLEARANCE
 BETWEEN ENCLOSURES FOR OPENING OF SIDE HINGED DOOR.
 * USE BOTH OUTER SWITCHING POLES.
 ‡ LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

CATALOG NUMBER	VOLTAGE RATINGS	AMPERE RATING	WIRING DIAG.	HORSEPOWER RATINGS										
				240VAC		480VAC				600VAC			250 * VDC	
				MAX.		STD.		MAX.		STD.	MAX.			
				1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	3Ø	1Ø	3Ø	STD.	MAX.
H361AWC	600VAC;250VDC	30	A	—	—	3	5	7 1/2	15	7 1/2	—	20	10	15
HU361AWC	600VAC;250VDC	30	B	5	10	—	—	10	20	—	15	30	—	10

HEAVY DUTY SAFETY SWITCHES
 WITH RECEPTACLE
 30 AMPERES-SERIES F7
 ENCLOSURE - NEMA TYPE 12/3R



DWG# 2212
 NO.