



TERMINAL LUGS			
AMPERES	MAX. WIRE	MIN. WIRE	TYPE
30	#2	#14	AL
60	#2	#14	AL
100	1/0 AWG	#14	AL

KNOCKOUTS			
SYMBOL	CONDUIT SIZE		DIAMETER
	IN	MM	
A	.50	13	.88 22
B	.75	19	1.13 29
C	1.00	25	1.38 35
D	1.25	32	1.75 44
E	1.50	38	2.00 51
F	2.00	51	2.50 64

DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATING	AMPERE RATING	WIRING DIAG	120 VAC		240 VAC				CORNER ③ GROUNDED DELTA SYSTEM		480 VAC				CORNER ③ GROUNDED DELTA SYSTEM		600 VAC				125 VDC ②		250 VDC ②		600 VDC ②	
				1PH ①		1PH ①		3PH				1PH ①		3PH				1PH ①		3PH							
				STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX
DTU361RB	600VAC : 600VDC	30	B	NA	2	NA	5	NA	10	NA	10	NA	7.5	NA	20	NA	20	NA	10	NA	30	NA	3	NA	5	NA	15
DTU362RB	600VAC : 600VDC	60	B	NA	5	NA	10	NA	20	NA	15	NA	25	NA	50	NA	30	NA	30	NA	60	NA	5	NA	10	NA	30
DTU223RB	240VAC : 250VDC	100	A	NA	NA	NA	15	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20	NA	NA
DTU323RB	240VAC : 250VDC	100	B	NA	NA	NA	15	NA	30	NA	30	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20	NA	NA
DTU363RB	600VAC : 600VDC	100	B	NA	7.5	NA	20	NA	40	NA	40	NA	40	NA	75	NA	60	NA	40	NA	75	NA	7.5	NA	20	40	50

NOTES:

UL LISTED - FILE E-2875

FINISH - GRAY BAKED ENAMEL

SHORT CIRCUIT CURRENT RATING:

10,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS H OR K FUSES.

200,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS J OR R FUSES.

① FOR SINGLE PHASE HP RATINGS USE 2 SWITCHING POLES.

② FOR DC RATINGS USE 2 SWITCHING POLES.

③ FOR CORNER GROUNDED DELTA SYSTEM, USE 2 SWITCHING POLES AND INSTALL NEUTRAL FOR GROUNDED CONDUCTOR.

DOUBLE THROW SAFETY SWITCHES  
VISIBLE BLADES  
30-100 AMPERE  
ENCLOSURE - TYPE 3R  
NOT FUSIBLE

**SQUARE D**  
**Schneider Electric**

DWG# 3202  
NO.