



Main

Range	PratiKa
Product or Component Type	Interlocked socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Complementary

Line Rated Current	125 A
[Ue] rated operational voltage	380...415 V
Network Frequency	50/60 Hz
Protection Type	Residual current breaker with overcurrent protection (RCBO)
Plug, socket material	Housing self-extinguishing engineering polymer
Connections - terminals	Captive screws
Cable cross section	0.02...0.15 in ² (16...95 mm ²)
Cable entry	Cable gland
Thread type	Pg 42
Net Weight	24.47 lb(US) (11.1 kg)
Height	27.95 in (710 mm)
Width	10.63 in (270 mm)
Depth	8.46 in (215 mm)
Color	Gray RAL 7035)
Voltage colour	Red

Environment

Standards	EN 60309-2 EN 60309-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 EN 62262
Fire resistance	1760 °F (960 °C) IEC 60695-2-11
Relative humidity	50 % 104 °F (40 °C) 70 % 86 °F (30 °C) 90 % 68 °F (20 °C)
Ambient air temperature for operation	95 °F (35 °C) 86400 s)




Ordering and shipping details

Category	00033-DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	3303430824442
Nbr. of units in pkg.	1
Package weight(Lbs)	24.47 lb(US) (11.1 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.42 in (29 cm)
Package 1 width	10.63 in (27 cm)
Package 1 Length	27.56 in (70 cm)

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------