

Main	
Range	PratiKa
Product or Component Type	Wander socket
Device short name	PratiKa socket
Plug, socket category	Extra-low voltage
Poles description	3P
Network type	AC
Outlet standard	Industrial

Complementary

Straight	
16 A	
4050 V	
50/60 Hz	
12 h	
Housing self-extinguishing engineering polymer	
Pins stainless steel Sleeves nickel plated brass Springs stainless steel	
Captive screws	
0.010.02 in ² (410 mm ²)	
0.240.91 in (623 mm)	
Cable gland	
Pg 21	
0.49 lb(US) (0.223 kg)	
2.87 in (73 mm)	
2.87 in (73 mm)	
6.26 in (159 mm)	
Gray RAL 7035)	
White	
	16 A 4050 V 50/60 Hz 12 h Housing self-extinguishing engineering polymer Pins stainless steel Sleeves nickel plated brass Springs stainless steel Captive screws 0.010.02 in² (410 mm²) 0.240.91 in (623 mm) Cable gland Pg 21 0.49 lb(US) (0.223 kg) 2.87 in (73 mm) 6.26 in (159 mm) Gray RAL 7035)

Environment

Standards	IEC 60309-2	
	IEC 60309-1	
IP degree of protection	IP67 conforming to IEC 60529	
IK degree of protection	IK08 EN 62262	
Fire resistance	1562 °F (850 °C) IEC 60695-2-1	
Relative humidity	50 % 104 °F (40 °C)	
	70 % 86 °F (30 °C)	
	90 % 68 °F (20 °C)	
Ambient air temperature for operation	95 °F (35 °C) 86400 s)	
	-13104 °F (-2540 °C)	

Ordering and shipping details

Category	00033-DT SWITCH,NEMA1	
Discount Schedule	DE1	
GTIN	3303430824541	
Nbr. of units in pkg.	1	
Package weight(Lbs)	7.05 oz (200 g)	
Returnability	No	
Country of origin	US	

Packing Units

PCE
2.83 in (7.2 cm)
2.83 in (7.2 cm)
5.71 in (14.5 cm)
BB1
10
4.67 lb(US) (2.12 kg)
4.65 in (11.8 cm)
8.27 in (21 cm)
10.83 in (27.5 cm)
S03
30
15.10 lb(US) (6.847 kg)
11.81 in (30 cm)
11.81 in (30 cm)
15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

outline training	
Warranty	18 months