


WIRING DIAGRAMS

FUSIBLE



NOT FUSIBLE



TERMINAL LUGS†

AMPERES	NAX. WIRE	MIN. WIRE	TYPE
60	#3 AWG	#12 AWG	AL
60	#3 AWG	#14 AWG	CU

KNOCKOUTS

SYMBOL	CONDUIT SIZE		DIAMETER	
	IN	MM	IN	MM
A	.50	13	.88	22
B	.75	19	1.13	29
C	1.00	25	1.38	35
D	1.25	32	1.75	45
E	1.50	38	2.00	51
F	2.00	51	2.50	64

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	AMPERE RATING	WIRING DIAG.	HORSEPOWER RATINGS										
				24DVAC		480VAC				600VAC			250 VDC	
				MAX.		STD.		MAX.		STD.	MAX.			
				10	30	10	30	10	30	30	10	30		
H362WC	600VAC;250VDC	60	A	—	—	5	15	20	30	15	—	50	10*	
HU362WC	600VAC;250VDC	60	B	10	20	—	—	25	50	—	30	60	—	

NOTES:
FINISH: SWITCHES — GRAY BAKED ENAMEL
CROUSE-HINDS RECEPTACLE — CAST ALUMINUM

UL LISTED — FILE E-2875

SHORT CIRCUIT CURRENT RATINGS:

10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES.

200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R OR J FUSES.

* USE BOTH OUTER SWITCHING POLES.

† LUGS SUITABLE FOR 60°C OR 75°C COPPER OR ALUMINUM CONDUCTORS.

HEAVY DUTY SAFETY SWITCHES
WITH RECEPTACLE
60 AMPERE—SERIES F6
ENCLOSURE — NEMA TYPE 1 GENERAL PURPOSE



SQUARE D COMPANY

DWG# 3134
NG.