

# Product data sheet

## Characteristics

# 8910DPA42V06

Contactor, Definite Purpose, 40A, 2 pole, 7.5 HP at 230 VAC, 1 phase, 440/480 VAC 50/60 Hz coil, open



## Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	40 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

## Complementary

Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 7.5 hp 230 V AC, 1 phase
Locked rotor rated current	240 A 277 V AC 200 A 460 V AC 160 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	1 phase
Electrical Connection	Box lugs Quick connect terminals

## Environment

Product Certifications	UL Recognized CSA
------------------------	----------------------

## Ordering and shipping details





Category	21344-8910 DPA 4_(40 AMP)
Discount Schedule	CP1B
GTIN	785901745600
Nbr. of units in pkg.	1
Package weight(Lbs)	15.20 oz (430.913 g)
Returnability	Yes
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.10 in (7.874 cm)
Package 1 width	2.50 in (6.35 cm)
Package 1 Length	3.90 in (9.906 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	7.86 lb(US) (3.565 kg)
Package 2 Height	6.90 in (17.526 cm)

Package 2 width	5.30 in (13.462 cm)
Package 2 Length	8.10 in (20.574 cm)

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

