# 8736SBO4V08

NEMA Starter, Type S, reversing, horizontal, Size 0, 18A, 5 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 208 VAC coil, open



Main		
Product Type	Starter	
Product Range	S	
Starter Type	Reversing	

Complementary

Complementary		
NEMA Size	0	
Rated Current	18 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	208 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	6.91 in (175.51 mm)	
Width	7.13 in (181.10 mm)	
Depth	5.31 in (134.87 mm)	

#### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA

### Ordering and shipping details

Category	21271 - 8702,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901519126
Nbr. of units in pkg.	1
Package weight(Lbs)	7.65 lb(US) (3.47 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	6.93 in (17.6 cm)	
Package 1 width	7.13 in (18.1 cm)	
Package 1 Length	5.31 in (13.5 cm)	

### Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

#### Contractual warranty

Warranty	18 months
----------	-----------