## 8502SAG11V02

NEMA Contactor, Type S, nonreversing, Size 00, 9A, 1 HP at 230 VAC, 1 phase, up to 100 kA, 2 pole, 120 VAC coil, NEMA 1



## Main

Product Type	Contactor	
Product Range	8502S	
Contactor Type	Non-reversing	

Complementary

Complementary		
NEMA Size	00	
Rated Current	9 A	
Number of Poles	2P	
Maximum Voltage Rating	600 V AC	
Phase	1 phase	
Horsepower Rating	0.33 HP 115 V AC 1 HP 230 V AC	
SCCR	Circuit-breaker 70 A maximum, SCCR: 100 kA at 480 V AC Fuse J 60 A maximum, SCCR: 100 kA at 600 V AC Fuse T 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 60 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	10.00 in (254 mm)	
Width	5.98 in (152 mm)	
Depth	5.28 in (134 mm)	

## Environmental

Enclosure Type	NEMA 1 painted sheet steel	
Certifications	UL listed file E78351 CCN NLDX CSA	

## Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	785901770695	
Nbr. of units in pkg.	1	
Package weight(Lbs)	6.44 lb(US) (2.92 kg)	

Returnability	No
Country of origin	MX
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
Contractual warranty	
Warranty	18 months