

Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	B
Insulation Temperature	365 °F (185 °C)
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	15 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	25 kA
Circuit Breaker Type	Secondary main breaker Feeder breaker Primary main breaker
Interior Type	QO Load Center interior
Number of Spaces Available	28
Number of Circuits	28
Enclosure Type	NEMA 3R hot-rolled steel




Ordering and shipping details

Category	16275-MPZ PLUG ON BRANCH CB
Discount Schedule	PE2
GTIN	785901403517
Nbr. of units in pkg.	1
Package weight(Lbs)	365.00 lb(US) (165.561 kg)
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	14.49 in (36.8 cm)
Package 1 width	19.13 in (48.6 cm)
Package 1 Length	44.61 in (113.3 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	 China RoHS Declaration
PVC free	Yes
Contractual warranty	
Warranty	18 months