8536SCG3V08E

NEMA Motor Starter, Type S, nonreversing, Size 1, 27A, 10 HP at 460 VAC, up to 65 kA SCCR, 3 phase, 3 pole, bimetal, 208 VAC coil, NEMA 1



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

o o i i pio i i o i i o i i o i i o i i o i i o i i o i i o i i o i i o i i o i i o i i o i o i o i o i o i o i		
NEMA Size	1	
Rated Current	27 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	IEC adapted Bi-metal	
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC	
SCCR	Circuit-breaker 60 A maximum, SCCR: 65 kA at 480 V AC Circuit-breaker 60 A maximum, SCCR: 50 kA at 600 V AC Fuse J 80 A maximum, SCCR: 65 kA at 600 V AC Fuse CC 80 A maximum, SCCR: 65 kA at 600 V AC	
Coil Voltage	208 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	10.00 in (254.00 mm)	
Width	6.00 in (152.40 mm)	
Depth	5.56 in (141.22 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901737704
Nbr. of units in pkg.	1
Package weight(Lbs)	6.90 lb(US) (3.13 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	6.00 in (15.24 cm)	
Package 1 width	6.70 in (17.018 cm)	
Package 1 Length	11.50 in (29.21 cm)	

Offer Sustainability

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
[™] REACh Declaration
Not compliant
China RoHS Declaration
Yes

Contractual warranty

Warranty	18 months