



Main

Product	Power Outlet Panel
Marketing Trade Name	Servicepak
Ampere Rating	100 A
Short Circuit Current Rating	10 kA
Phase	1 phase
Voltage Rating	120/240 V AC

Complementary

Certifications	UL Listed
Application	Recreational vehicle park sites
Enclosure Rating	NEMA 3R
Electrical Connection	Screw clamp terminal
Wire Size	AWG 6...250 kcmil aluminium AWG 6...250 kcmil copper
Mounting	Pedestal
Outlet Configuration	14C

Ordering and shipping details

Category	00034-PAK DEVICES
Discount Schedule	DE4
GTIN	785901477341
Nbr. of units in pkg.	1
Package weight(Lbs)	40.90 lb(US) (18.552 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.98 in (15.2 cm)
Package 1 width	8.58 in (21.8 cm)
Package 1 Length	68.50 in (174 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------