8536SBH2V08

NEMA Motor Starter, Type S, nonreversing, Size 0, 18A, 5 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 208 VAC coil, NEMA 3R



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

NEMA Size 0 Rated Current 18 A Number of Poles 3P Maximum Voltage Rating 600 V AC Phase 3 phase Type of Overload Melting alloy 3 Horsepower Rating 3 HP 200 V AC 3 HP 230 V AC 5 HP 60 V AC 5 HP 60 V AC 5 HP 575 V AC SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm) Depth 7.13 in (181.10 mm)			
Number of Poles 3P Maximum Voltage Rating 600 V AC Phase 3 phase Type of Overload Melting alloy 3 Horsepower Rating 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	NEMA Size	0	
Maximum Voltage Rating 600 V AC Phase 3 phase Type of Overload Melting alloy 3 Horsepower Rating 3 HP 200 V AC 5 HP 460 V AC 5 HP 575 V AC SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Rated Current	18 A	
Phase 3 phase Type of Overload Melting alloy 3 Horsepower Rating 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 460 V AC 5 HP 575 V AC SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Number of Poles	3P	
Type of Overload Horsepower Rating 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width	Maximum Voltage Rating	600 V AC	
Horsepower Rating 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Phase	3 phase	
3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Type of Overload	Melting alloy 3	
Fuse: 5 kA at 600 V AC Coil Voltage 208 V AC 60 Hz Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Horsepower Rating	3 HP 230 V AC 5 HP 460 V AC	
Control Circuit Type Common control circuit Control Units No control units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	SCCR		
Control Units Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Coil Voltage	208 V AC 60 Hz	
Pilot Light Without pilot light Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Control Circuit Type	Common control circuit	
Auxiliary Contacts Without Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Control Units	No control units	
Terminal Type Screw clamp terminals Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Pilot Light	Without pilot light	
Height 12.28 in (311.91 mm) Width 8.84 in (224.54 mm)	Auxiliary Contacts	Without	
Width 8.84 in (224.54 mm)	Terminal Type	Screw clamp terminals	
	Height	12.28 in (311.91 mm)	
Depth 7.13 in (181.10 mm)	Width	8.84 in (224.54 mm)	
	Depth	7.13 in (181.10 mm)	

Environment

Enclosure Type	NEMA 3R painted sheet steel
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	785901824640	
Nbr. of units in pkg.	1	
Package weight(Lbs)	13.89 lb(US) (6.3 kg)	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	12.28 in (31.2 cm)	
Package 1 width	8.86 in (22.5 cm)	
Package 1 Length	7.13 in (18.1 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☐ REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	☐ China RoHS Declaration	
PVC free	Yes	

Contractual warranty

Warranty	18 months