8702SBO2V02S

NEMA Contactor, Type S, reversing, horizontal, Size 0, 18A, 2 HP at 230 VAC, single phase, up to 100 kA, 3 pole, 120 VAC coil, open style



Main

Product Type	Contactor
Product Range	Type S
Contactor Type	Reversing

Complementary

Complementary		
NEMA Size	0	
Rated Current	18 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	4 wires	
Maximum Voltage Rating	600 V AC	
Phase	1 phase	
Motor Type	Repulsion induction	
Horsepower Rating	1 HP 115 V AC 2 HP 230 V AC	
SCCR	Circuit-breaker 70 A maximum, SCCR: 100 kA at 480 V AC Fuse J 60 A maximum, SCCR: 100 kA at 600 V AC Fuse T 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 60 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	5.00 in (127.00 mm)	
Width	7.13 in (181.10 mm)	
Depth	5.31 in (134.87 mm)	

Environment

	Enclosure Type	Not rated (open device)
Certifications UL Listed CSA	Certifications	

Ordering and shipping details

21271 - 8702,36 SA,SB(NOT S*R,T,W)	
CP1	
785901610342	
1	
11.00 lb(US) (4.99 kg)	
No	
MX	
	CP1 785901610342 1 11.00 lb(US) (4.99 kg) No

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.00 in (12.7 cm)	
Package 1 width	7.13 in (18.1 cm)	
Package 1 Length	5.31 in (13.5 cm)	

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------