8736SBO4V01S

NEMA Starter, Type S, reversing, horizontal, Size 0, 18A, 5 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 24 VAC coil, open



Main

Product Type	Starter	
Product Range	S	
Starter Type	Reversing	

Complementary

NEMA Size	0	
Rated Current	18 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	24 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	6.91 in (175.51 mm)	
Width	7.13 in (181.10 mm)	
Depth	5.31 in (134.87 mm)	

Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA

Ordering and shipping details

Category	21271 - 8702,36 SA,SB(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	785901724469	
Nbr. of units in pkg.	1	
Package weight(Lbs)	7.65 lb(US) (3.470 kg)	
Returnability	No	
Country of origin	MX	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	

Contractual warranty

Warranty	18 m	onths